

# HJ 50 G 15 | Cylinder

| Specifications                   |         |              |
|----------------------------------|---------|--------------|
| article number                   |         | 100.112.035  |
| short description                |         | Cylinder     |
| model                            |         | HJ 50 G 15   |
| max. working pressure            | psi     | 10443        |
| tonnage                          | lb      | 110231.0     |
| stroke                           | in      | 5.9          |
| closed height                    | in      | 11.1         |
| capacity                         | lbf     | 114720       |
| effective pressure area          | sq. in. | 11           |
| required oil content (effective) | oz      | 36           |
| connection                       |         | A 118        |
| cylinder type                    |         | high tonnage |
| acting type                      |         | single       |
| return type                      |         | gravity      |
| material                         |         | steel        |
| weight, ready for use            | lb      | 59.5         |

| Technical drawing dimensions |    |      |
|------------------------------|----|------|
| dimension A                  | in | 11.1 |
| dimension B                  | in | 5.1  |
| dimension C                  | in | 3.1  |
| dimension D                  | in | 2.8  |
| dimension E                  | in | 1    |
| dimension F                  | in | 10.8 |
| I type                       |    | [I2] |

| Standard supplied with                                                                                   |  |
|----------------------------------------------------------------------------------------------------------|--|
| <ul style="list-style-type: none"> <li>• High flow female coupler A118</li> <li>• Flat saddle</li> </ul> |  |

| Accessories            |             |
|------------------------|-------------|
| Tilting Saddle S 50 TN | 100.181.043 |

