

Technical specification sheet

HHJ 20 S 15 | Hollow Plunger Cylinder

| Specifications | | |
|----------------------------------|-----------------|-------------------------|
| article number | | 100.112.030 |
| short description | | Hollow Plunger Cylinder |
| model | | HHJ 20 S 15 |
| max. working pressure | bar/Mpa | 720 / 72 |
| tonnage | t | 20 |
| stroke | mm | 150 |
| closed height | mm | 389 |
| capacity | kN/t | 223.9 / 22.8 |
| effective pressure area | cm ² | 31.1 |
| required oil content (effective) | cc | 467 |
| connection | | A 118 |
| cylinder type | | hollow plunger |
| acting type | | single |
| return type | | spring |
| material | | steel |
| weight, ready for use | kg | 18.0 |

| Technical drawing dimensions | | |
|------------------------------|------------|---------|
| dimension A | mm | 389 |
| dimension B | mm | 100 |
| dimension C | mm | 50 |
| dimension D | mm | 90 |
| dimension E | mm | 31 |
| dimension F | mm | 377 |
| dimension R | mm | 27 |
| dimension S | threadsize | M38x1,5 |
| I type | | [I2] |

Standard supplied with

- High flow female coupler A118
- Hollow saddle (with the exception of the HHJ5S2.5, HHJ12S5 and HHJ12S15)

