

HAHC100H25 | Aluminum Hollow Plunger Cylinder

Specifications		
article number		100.112.385
short description		Aluminum Hollow Plunger Cylinder
model		HAHC100H25
max. working pressure	psi	10443
tonnage	lb	220462.0
stroke	in	9.8
closed height	in	16.9
capacity	lbf	231328
capacity (retract)	lbf	96893
effective pressure area (press)	sq. in.	22.1
effective pressure area (retract)	sq. in.	9.3
required oil content (effective)	oz	70.2
required oil content (press)	oz	120.9
required oil content (retract)	oz	50.6
connection		A 118
cylinder type		hollow plunger
acting type		double
return type		hydraulic
material		aluminium
weight, ready for use	lb	112.9
ASME		B30.1

Technical drawing dimensions		
dimension A	in	16.9
dimension B	in	9.6
dimension C	in	5.5
dimension D	in	3.1
dimension E	in	1.6
dimension F	in	16.3
dimension G	in	3.5
dimension P	in	2.7
dimension R	in	3.1

Standard supplied with	
• High flow female coupler A118 • Hollow saddle; prevents damage to the plunger • Larger cylinders are equipped with foldable handles for easy carrying and positioning	

Accessories	
Saddle TRS100	101.000.762

