

Technical specification sheet

12W6P Asia | Vari Pump

| Specifications | | |
|-------------------------------|-----|----------------------------|
| article number | | 101.002.113 |
| model | | 12W6P Asia |
| max. working pressure | psi | 10443 |
| short description | | Vari Pump |
| capacity oil tank (effective) | oz | 202.9 |
| number of outputs | | 1 |
| number of stages | | 2 |
| first stage output / min. | oz | 121.7 |
| second stage output / min. | oz | 44 |
| first stage pressure range | psi | 0 - 2901 |
| second stage pressure range | psi | 2901 - 10443 |
| operator type | | petrol engine |
| engine | | 4-stroke - 4.2 HP - 3.1 kW |
| weight, ready for use | lb | 81.6 |
| dimensions (LxWxH) | in | 18.5 x 13.6 x 18.6 |

| Required Accessories | | |
|---------------------------------------|--|-------------|
| Control Valve - Single Acting - M 311 | | 100.181.311 |
| Control Valve - Double Acting - M 322 | | 100.181.322 |

| Accessories | | |
|---|--|-------------|
| Single-/Double Acting Valve (SADA) M 304 | | 100.172.051 |
| Control Valve - Double Acting - M 323 (Deadmans Function) | | 100.181.323 |
| Remote Control Valve + Oil Filter - Double Acting - M 326 | | 100.182.321 |
| Pressure Control Valve M 303 | | 100.181.303 |

