



Maintenance: after use | T1 | 26963



### Prerequisites before repair:

- Only Holmatro trained and certified technicians are allowed to perform this task.
- Wear full protective gear during maintenance.
- Always act according to the instructions supplied with each tool.

### Necessary equipment;

1		<p><b>Check:</b></p> <ul style="list-style-type: none"><li>- General condition</li><li>- Oil leakage</li><li>- Damages that can interfere with functioning or safety</li><li>- Dirt: clean if necessary</li><li>- Readability of the identification / safety label, replace if unreadable</li></ul>
2		<p><b>Check:</b></p> <ul style="list-style-type: none"><li>- Check the proper functioning of the pump rod and lever.</li><li>- Check it moves smoothly (without pushing or friction) and easily returns to neutral position.</li></ul>
3		<p><b>Check:</b></p> <ul style="list-style-type: none"><li>- Check the blades (1) for damage</li><li>- Clean hinge pin (2). Check the snap ring of the hinge pin for; damages, corrosion and wear.</li></ul>

Holmatro Rescue Equipment B.V. | P.O. Box 33 | 4940 AA Raamsdonksveer, the Netherlands | T +31 (0)162 589200 | rescue@holmatro.com | www.holmatro.com

While the greatest care has been devoted to the content, it is possible that the information in this printed matter is incorrect or incomplete. N.V. Holmatro and its affiliated companies (hereafter: Holmatro) cannot be held liable in any way for the consequences of activities undertaken on the basis of this printed matter. If you have any doubts about the correctness or completeness of the information, you shall contact Holmatro. Nothing from this printed matter can be copied and/or made public in any way without the explicit authorization of Holmatro.

<p>4</p>		<p><b>Check:</b></p> <ul style="list-style-type: none"> <li>- Check the toe and body (1) for damage.</li> <li>- Check the wedge (2) for damage and spray Teflon lubricating oil on the push button while operating</li> <li>- Spray Teflon oil on the moving points of the tool (3).</li> </ul>
<p>5</p>		<p><b>Assemble:</b></p> <ul style="list-style-type: none"> <li>- Check that the toe and body are in completely closed position and store the tool.</li> <li>- Preserve the tool with WD-40 multispray against corrosion.</li> </ul>