


Technical specification sheet

HBC100A30 | Battery Cutter

Specifications		
article number		101.003.238
model		HBC100A30
max. working pressure	psi	7252
blade type		30 standard
cutter type		Battery
short description		Battery Cutter
battery included		Yes, 2 pcs
connectivity, mobile app		Bluetooth
max. cutting force	lbf	125219
max. cutting opening	in	6.7
protection rate		IP57
sound emission @ 1m/3.25ft	dB(A)	75
sound emission @ 4m/13ft	dB(A)	66
required oil content (effective)	oz	6.4
hydraulic oil type		ISO-L HV VG 36
weight, ready for use	lb	41.4
dimensions (LxWxH)	in	32.8 x 10.7 x 10.9
temperature range	°F	-4 +131
max. cutting diameter round bar (S235 acc. to EN 10025-2)	in	1
max. cutting diameter round tube (E235 acc. to EN 10305-1) based on wall thickness 3mm/0,12in.	in	3.1
catalytic converter	%	95
number of cuts per day		50
number of operating hours per day		4



Technical drawing dimensions		
dimension A	in	32.8
dimension B	in	10.7
dimension C	in	10.9

Required Accessories	
Battery Charger PBCH1 (AC-EU)	101.003.242
Battery Charger PBCH5 (AC-UK)	101.003.243
Battery Charger PBCH2 (AC-US)	101.003.244

Accessories	
Set blades HMC/HBC100A10	101.003.253
Carrying strap HBC cutters	101.003.351



holmatro.com

© Holmatro 2026-01-17

While the greatest care has been devoted to the content, it is possible that the information in this printed matter is incorrect or incomplete. Holmatro B.V. and its affiliated companies (hereafter: Holmatro) cannot be held liable in any way for the consequences of activities undertaken on the basis of this printed matter. Values can vary within the manufacturer measurements. If you have any doubts about the correctness or completeness of the information, you shall contact Holmatro (T +31 (0)162-751480). Nothing from this printed matter can be copied and/or made public in any way without the explicit authorisation of Holmatro.