

Technical specification sheet


HBC100A10 | Battery Cutter

Specifications		
article number		101.003.235
model		HBC100A10
blade type		10 cable
cutter type		Battery
short description		Battery Cutter
battery included		Yes, 2 pcs
connectivity, mobile app		Bluetooth
max. working pressure	bar/Mpa	500 / 50
max. cutting opening	mm	145
max. cutting force	kN/t	559 / 57
protection rate		IP57
sound emission @ 1m/3.25ft	dB(A)	75
sound emission @ 4m/13ft	dB(A)	66
required oil content (effective)	cc	189
hydraulic oil type		ISO-L HV VG 36
weight, ready for use	kg	19.8
dimensions (LxWxH)	mm	859 x 271 x 276
temperature range	°C	-20 +55
weight (excl. battery)	kg	18.3
max. cutting diameter power cable	mm	110
number of cuts per day		50
number of operating hours per day		4

Technical drawing dimensions		
dimension A	mm	859
dimension B	mm	271
dimension C	mm	276

Required Accessories	
Battery Charger PBCH1 (AC-EU)	101.003.242
Battery Charger PBCH5 (AC-UK)	101.003.243
Battery Charger PBCH2 (AC-US)	101.003.244

Accessories	
Set blades HMC/HBC100A30	101.003.256
Carrying strap HBC cutters	101.003.351



[holmatro.com](https://www.holmatro.com)

© Holmatro 2026-01-17

While the greatest care has been devoted to the content, it is possible that the information in this printed matter is incorrect or incomplete. Holmatro B.V. and its affiliated companies (hereafter: Holmatro) cannot be held liable in any way for the consequences of activities undertaken on the basis of this printed matter. Values can vary within the manufacturer measurements. If you have any doubts about the correctness or completeness of the information, you shall contact Holmatro (T +31 (0)162-751480). Nothing from this printed matter can be copied and/or made public in any way without the explicit authorisation of Holmatro.