

Technical specification sheet


HBC400A30 | Battery Cutter

Specifications		
article number		101.003.239
model		HBC400A30
blade type		30 standard
cutter type		Battery
short description		Battery Cutter
battery included		Yes, 2 pcs
connectivity, mobile app		Bluetooth
max. working pressure	bar/Mpa	500 / 50
max. cutting opening	mm	182
max. cutting force	kN/t	977 / 99.6
protection rate		IP57
sound emission @ 1m/3.25ft	dB(A)	75
sound emission @ 4m/13ft	dB(A)	66
required oil content (effective)	cc	290
hydraulic oil type		ISO-L HV VG 36
weight, ready for use	kg	21.5
dimensions (LxWxH)	mm	890 x 271 x 276
temperature range	°C	-20 +55
weight (excl. battery)	kg	20.0
max. cutting diameter round bar (S235 acc. to EN 10025-2)	mm	30
max. cutting diameter round tube (E235 acc. to EN 10305-1) based on wall thickness 3mm/0,12in.	mm	100
max. cutting diameter round tube (E235 acc. to EN 10305-1), based on wall thickness 5mm/0,2in	mm	60
catalytic converter	%	100
number of cuts per day		50
number of operating hours per day		4

Technical drawing dimensions		
dimension A	mm	890
dimension B	mm	271
dimension C	mm	276

Required Accessories		
Battery Charger PBCH1 (AC-EU)		101.003.242
Battery Charger PBCH5 (AC-UK)		101.003.243
Battery Charger PBCH2 (AC-US)		101.003.244

Accessories		
Set blades HMC/HBC400A10		101.003.254
Carrying strap HBC cutters		101.003.351



holmatro.com

© Holmatro 2026-01-17

While the greatest care has been devoted to the content, it is possible that the information in this printed matter is incorrect or incomplete. Holmatro B.V. and its affiliated companies (hereafter: Holmatro) cannot be held liable in any way for the consequences of activities undertaken on the basis of this printed matter. Values can vary within the manufacturer measurements. If you have any doubts about the correctness or completeness of the information, you shall contact Holmatro (T +31 (0)162-751480). Nothing from this printed matter can be copied and/or made public in any way without the explicit authorisation of Holmatro.