


Technical specification sheet

HMC050A30 | Mobile Cutter

Specifications		
article number		101.003.217
model		HMC050A30
blade type		30 standard
cutter type		mobile
short description		Mobile Cutter
battery included		no
max. working pressure	bar/Mpa	500 / 50
max. cutting opening	mm	170
max. cutting force	kN/t	438 / 44.7
required oil content (effective)	cc	155
hydraulic oil type		ISO-L HV VG 36
weight, ready for use	kg	10.8
dimensions (LxWxH)	mm	693 x 254 x 240
temperature range	°C	-20 +55
max. cutting diameter round bar (S235 acc. to EN 10025-2)	mm	22
max. cutting diameter round tube (E235 acc. to EN 10305-1) based on wall thickness 3mm/0,12in.	mm	60
catalytic converter	%	90
number of cuts per day		100
number of operating hours per day		8

Technical drawing dimensions		
dimension A	mm	693
dimension B	mm	254
dimension C	mm	240

Accessories		
Set blades HMC/HBC050A10		101.003.252



[holmatro.com](https://www.holmatro.com)

© Holmatro 2026-01-17

While the greatest care has been devoted to the content, it is possible that the information in this printed matter is incorrect or incomplete. Holmatro B.V. and its affiliated companies (hereafter: Holmatro) cannot be held liable in any way for the consequences of activities undertaken on the basis of this printed matter. Values can vary within the manufacturer measurements. If you have any doubts about the correctness or completeness of the information, you shall contact Holmatro (T +31 (0)162-751480). Nothing from this printed matter can be copied and/or made public in any way without the explicit authorisation of Holmatro.