

Technical specification sheet

HBPO5C02 | APEIRON Holmatro Battery Pump

Specifications		
article number		101.003.448
model		HBPO5C02
equipped with (connector type)		dual hoses
for cutter type		mobile
short description		APEIRON Holmatro Battery Pump
max. working pressure	bar/Mpa	500 / 50
battery included		Yes, 2 pcs
connectivity, mobile app		Bluetooth
number of stages		stepless
high pressure output / min	cc	700
low pressure output / min	cc	3100
capacity oil tank	cc	2500
capacity oil tank (effective)	cc	2000
protection rate		IP44
sound emission @ 1m/3.25ft	dB(A)	75
sound emission @ 4m/13ft	dB(A)	61
operator type		battery
couplers		yes
number of tool connections		1
hydraulic oil type		ISO-L HV VG 36
engine		28 VDC - 0.95 kW
weight, ready for use	kg	13.3
dimensions (LxWxH)	mm	520 x 234 x 260
temperature range	°C	-20 +55
dimensions (AxBxC)	mm	520 x 260 x 234
weight (excl. battery)	kg	11.7

Standard supplied with

- 2 Batteries
- Couplers that suit the application: plug and play

Required Accessories

Battery Charger PBCH1 (AC-EU)	101.003.242
Battery Charger PBCH5 (AC-UK)	101.003.243
Battery Charger PBCH2 (AC-US)	101.003.244

