

Technical specification sheet


HJ 200 H 15 | Cylinder

Specifications		
article number		100.122.071
short description		Cylinder
model		HJ 200 H 15
max. working pressure	bar/MPa	720 / 72
tonnage	t	200
stroke	mm	150
closed height	mm	327
capacity	kN/t	2040.6 / 208.1
effective pressure area (press)	cm ²	283.5
effective pressure area (retract)	cm ²	82.5
required oil content (effective)	cc	3015
required oil content (press)	cc	4253
required oil content (retract)	cc	1238
connection		A 118
cylinder type		high tonnage
acting type		double
return type		hydraulic
material		steel
weight, ready for use	kg	121.0

Technical drawing dimensions		
dimension A	mm	327
dimension B	mm	261
dimension C	mm	160
dimension D1	mm	70
dimension D2	mm	85
dimension E	mm	60
dimension F	mm	320
dimension P	mm	60
I type		[I1]

Standard supplied with	
• High Flow female coupler A 118 on inlet port • High Flow female coupler with pressure relief valve A 418 on outlet port • Flat saddle	

Accessories	
Tilting Saddle HJ 200 - 250 (SN)	100.999.040



holmatro.com

© Holmatro 2026-08-13

While the greatest care has been devoted to the content, it is possible that the information in this printed matter is incorrect or incomplete. Holmatro B.V. and its affiliated companies (hereafter: Holmatro) cannot be held liable in any way for the consequences of activities undertaken on the basis of this printed matter. Values can vary within the manufacturer measurements. If you have any doubts about the correctness or completeness of the information, you shall contact Holmatro (T +31 (0)162-751480). Nothing from this printed matter can be copied and/or made public in any way without the explicit authorisation of Holmatro.