

Technical specification sheet


HJ 150 G 15 | Cylinder

Specifications		
article number		100.112.046
short description		Cylinder
model		HJ 150 G 15
max. working pressure	bar/MPa	720 / 72
tonnage	t	150
stroke	mm	150
closed height	mm	317
capacity	kN/t	1538.9 / 156.9
effective pressure area	cm ²	213.8
required oil content (effective)	cc	3207
connection		A 118
cylinder type		high tonnage
acting type		single
return type		gravity
material		steel
weight, ready for use	kg	74.6

Technical drawing dimensions		
dimension A	mm	317
dimension B	mm	227
dimension C	mm	115
dimension D	mm	70
dimension E	mm	57
dimension F	mm	310
I type		[I1]

Standard supplied with	
• High flow female coupler A118 • Flat saddle	

Accessories	
Tilting Saddle HJ 100 - 150 (SN)	100.181.044



holmatro.com

© Holmatro 2026-08-13

While the greatest care has been devoted to the content, it is possible that the information in this printed matter is incorrect or incomplete. Holmatro B.V. and its affiliated companies (hereafter: Holmatro) cannot be held liable in any way for the consequences of activities undertaken on the basis of this printed matter. Values can vary within the manufacturer measurements. If you have any doubts about the correctness or completeness of the information, you shall contact Holmatro (T +31 (0)162-751480). Nothing from this printed matter can be copied and/or made public in any way without the explicit authorisation of Holmatro.