

Technical specification sheet

IPU-S32S25E-EC | Extremely Durable Pump

Specifications		
article number		101.002.639
model		IPU-S32S25E-EC
max. working pressure	bar/MPa	350 / 35
for cutter type		stationary HSC200STH40
short description		Extremely Durable Pump
capacity oil tank (effective)	cc	25000
number of stages		1
first stage output / min.	cc	3200
first stage pressure range	bar/MPa	0 - 350 / 0 - 35
operator type		electric motor
engine		400 VAC - 2.2 kW - 50 Hz - 3 Ph
speed	rpm	2850
weight, ready for use	kg	120.0
dimensions (AxBxC)	mm	523 x 640 x 650

Technical drawing dimensions		
dimension A	mm	523
dimension B	mm	640
dimension C	mm	650

Accessories		
Pressure Relief Tool A239		150.182.016



[holmatro.com](https://www.holmatro.com)

© Holmatro 2026-08-24

While the greatest care has been devoted to the content, it is possible that the information in this printed matter is incorrect or incomplete. Holmatro B.V. and its affiliated companies (hereafter: Holmatro) cannot be held liable in any way for the consequences of activities undertaken on the basis of this printed matter. Values can vary within the manufacturer measurements. If you have any doubts about the correctness or completeness of the information, you shall contact Holmatro (T +31 (0)162-751480). Nothing from this printed matter can be copied and/or made public in any way without the explicit authorisation of Holmatro.