

Technical specification sheet

HBC400A30 | Battery Cutter

Specifications		
article number		101.003.239
model		HBC400A30
blade type		30 standard
cutter type		Battery
short description		Battery Cutter
battery included		Yes, 2 pcs
connectivity, mobile app		Bluetooth
max. working pressure	bar/MPa	500 / 50
max. cutting opening	mm	182
max. cutting force	kN/t	977 / 99.6
protection rate		IP57
sound emission @ 1m/3.25ft	dB(A)	75
sound emission @ 4m/13ft	dB(A)	66
required oil content (effective)	cc	290
hydraulic oil type		ISO-L HV VG 36
weight, ready for use	kg	21.5
dimensions (LxWxH)	mm	890 x 271 x 276
temperature range	°C	-20 +55
weight (excl. battery)	kg	20.0
max. cutting diameter round bar (S235 acc. to EN 10025-2)	mm	30
max. cutting diameter round tube (E235 acc. to EN 10305-1) based on wall thickness 3mm/0,12in.	mm	100
max. cutting diameter round tube (E235 acc. to EN 10305-1), based on wall thickness 5mm/0,2in	mm	60
catalytic converter	%	100
number of cuts per day		50
number of operating hours per day		4

Technical drawing dimensions		
dimension A	mm	890
dimension B	mm	271
dimension C	mm	276

Required Accessories		
Battery Charger PBCH1 (AC-EU)		101.003.242
Battery Charger PBCH5 (AC-UK)		101.003.243
Battery Charger PBCH2 (AC-US)		101.003.244

Accessories		
Set blades HMC/HBC400A10		101.003.254
Carrying strap HBC cutters		101.003.351

