

Technical specification sheet

PA 100 H 2 | Hand Pump

Specifications

article number		101.000.331
short description		Hand Pump
model		PA 100 H 2
max. working pressure	bar/MPa	550 / 55
capacity oil tank (effective)	cc	10000
capacity oil tank	cc	6150
number of stages		2
first stage output (per stroke)	cc	50.5
second stage output (per stroke)	cc	4
first stage pressure range	bar/MPa	0 - 45 / 0 - 4.5
second stage pressure range	bar/MPa	45 - 550 / 4.5 - 55
max. operating force	kg	34.0
operator type		hand
double acting optional		yes
number of tool connections		2
weight, ready for use	kg	21.2

Technical drawing dimensions

dimension A	mm	1123
dimension B	mm	210
dimension C	mm	184

Standard supplied with

- Double acting valve VM 43 L
- Flare face couplers



holmatro.com

© Holmatro 2026-08-13

While the greatest care has been devoted to the content, it is possible that the information in this printed matter is incorrect or incomplete. Holmatro B.V. and its affiliated companies (hereafter: Holmatro) cannot be held liable in any way for the consequences of activities undertaken on the basis of this printed matter. Values can vary within the manufacturer measurements. If you have any doubts about the correctness or completeness of the information, you shall contact Holmatro (T +31 (0)162-751480). Nothing from this printed matter can be copied and/or made public in any way without the explicit authorisation of Holmatro.