

Technical specification sheet

12 W 25 E | Vari Pump

Specifications		
article number		100.152.064
model		12 W 25 E
max. working pressure	psi	10443
short description		Vari Pump
capacity oil tank (effective)	oz	845.4
number of outputs		1
number of stages		2
first stage output / min.	oz	108.2
second stage output / min.	oz	40.6
first stage pressure range	psi	0 - 2901
second stage pressure range	psi	2901 - 10443
operator type		electric motor
engine		400 VAC - 1.5 kW - 50 Hz - 3 Ph
speed	rpm	2850
weight, ready for use	lb	141.1
dimensions (LxWxH)	in	19.7 x 15 x 21.3

Required Accessories	
Control Valve - Single Acting - M 311	100.181.311
Control Valve - Double Acting - M 322	100.181.322

Accessories	
Single-/Double Acting Valve (SADA) M 304	100.172.051
Control Valve - Double Acting - M 323 (Deadmans Function)	100.181.323
Remote Control Valve + Oil Filter - Double Acting - M 326	100.182.321
Pressure Control Valve M 303	100.181.303



holmatro.com

© Holmatro 2024-04-16

While the greatest care has been devoted to the content, it is possible that the information in this printed matter is incorrect or incomplete. Holmatro B.V. and its affiliated companies (hereafter: Holmatro) cannot be held liable in any way for the consequences of activities undertaken on the basis of this printed matter. Values can vary within the manufacturer measurements. If you have any doubts about the correctness or completeness of the information, you shall contact Holmatro (T +31 (0)162-751480). Nothing from this printed matter can be copied and/or made public in any way without the explicit authorisation of Holmatro.