Technical specification sheet

12W6P Asia Vari Pump

Specifications		
article number		101.002.113
model		12W6P Asia
max. working pressure	bar/Mpa	720 / 72
short description		Vari Pump
capacity oil tank (effective)	CC	6000
number of outputs		1
number of stages		2
first stage output / min.	CC	3600
second stage output / min.	CC	1300
first stage pressure range	bar/Mpa	0 - 200 / 0 - 20
second stage pressure range	bar/Mpa	200 - 720 / 20 - 72
operator type		petrol engine
engine		4-stroke - 4.2 HP - 3.1 kW
weight, ready for use	kg	37.0
dimensions (LxWxH)	mm	470 x 346 x 472



100.181.311
100.181.322

Accessories		
Single-/Double Acting Valve (SADA) M 304	100.172.051	
Control Valve - Double Acting - M 323 (Deadmans Function)	100.181.323	
Remote Control Valve + Oil Filter - Double Acting - M 326	100.182.321	
Pressure Control Valve M 303	100.181.303	

holmatro.com

© Holmatro 2024-04-16

While the greatest care has been devoted to the content, it is possible that the information in this printed matter is incorrect or incomplete. Holmatro B.V. and its affiliated companies (hereafter: Holmatro) cannot be held liable in any way for the consequences of activities undertaken on the basis of this printed matter. Values can vary within the manufacturer measurements. If you have any doubts about the correctness or completeness of the information, you shall contact Holmatro (T +31 (0)162-751480). Nothing from this printed matter can be copied and/or made public in any way without the explicit authorisation of Holmatro.

