Technical specification sheet

BCU 05 A 30 | Battery Cutter


Specifications		
article number		170.012.127
model		BCU 05 A 30
max. working pressure	psi	7252
blade type		30 standard
cutter type		mobile
short description		Battery Cutter
battery included		no
max. cutting force	lbf	27876
max. cutting opening	in	3.9
protection rate		IP54
sound emission @ 1m/3.25ft	dB(A)	124
sound emission @ 4m/13ft	dB(A)	65
required oil content (effective)	OZ	1.3
weight, ready for use	lb	30.4
temperature range	°F	-4 +131

Technical drawing dimensions				
dimension A	in	28.1		
dimension B	in	10.9		
dimension C	in	8		

Required Accessories		
Greenline Battery Charger BCH1	150.182.208	
Greenline Battery Charger BCH2	150.182.209	
Greenline Battery Charger BCH3	150.182.286	
Greenline Battery BPA286	151.000.307	

Accessories	
Carrying Strap	150.182.249
Blades, Set 10 Cable (ICU 05)	170.013.058







holmatro.com

© Holmatro 2024-04-27

While the greatest care has been devoted to the content, it is possible that the information in this printed matter is incorrect or incomplete. Holmatro B.V. and its affiliated companies (hereafter: Holmatro) cannot be held liable in any way for the consequences of activities undertaken on the basis of this printed matter. Values can vary within the manufacturer measurements. If you have any doubts about the correctness or completeness of the information, you shall contact Holmatro (T +31 (0)162-751480). Nothing from this printed matter can be copied and/or made public in any way without the explicit authorisation of Holmatro.

