
Technical specification sheet

HAHC20S15 Aluminum Hollow Plunger Cylinder

| Specifications | | |
|----------------------------------|-----------------|-------------------------------------|
| article number | | 100.112.368 |
| short description | | Aluminum Hollow Plunger Cylinder |
| model | | HAHC20S15 |
| max. working pressure | bar/Mpa | 720 / 72 |
| tonnage | t | 20 |
| stroke | mm | 150 |
| closed height | mm | 310 |
| capacity | kN/t | 208 / 21.2 |
| effective pressure area | Cm ² | 28.9 |
| required oil content (effective) | CC | 433 |
| connection | | A 118 |
| cylinder type | | hollow plunger |
| acting type | | single |
| return type | | spring |
| material | | aluminium |
| weight, ready for use | kg | 5.5 |
| ASME | | B30.1 |





| Technical drawing dimensions | | |
|------------------------------|----|------|
| dimension A | mm | 310 |
| dimension B | mm | 98 |
| dimension C | mm | 63 |
| dimension D | mm | 80 |
| dimension E | mm | 24.5 |
| dimension F | mm | 246 |
| dimension G | mm | 43.5 |
| dimension H | mm | 150 |
| dimension R | mm | 27 |
| angle A1 | 0 | 45 |

Standard supplied with

High flow female coupler A118Hollow saddle; prevents damage to the plunger

• Larger cylinders are equipped with foldable handles for easy carrying and positioning

Accessories

Saddle TRS20

100.003.650



holmatro.com

© Holmatro 2023-11-29

While the greatest care has been devoted to the content, it is possible that the information in this printed matter is incorrect or incomplete. Holmatro B.V. and its affiliated companies (hereafter: Holmatro) cannot be held liable in any way for the consequences of activities undertaken on the basis of this printed matter. Values can vary within the manufacturer measurements. If you have any doubts about the correctness or completeness of the information, you shall contact Holmatro (T+31 (0)162-751480). Nothing from this printed matter can be copied and/or made public in any way without the explicit authorisation of Holmatro.

