## **Technical specification sheet**

# HAHC60S15 Aluminum Hollow Plunger Cylinder


Specifications			
article number		100.112.378	
short description		Aluminum Hollow Plunger Cylinder	
model		HAHC60S15	
max. working pressure	bar/Mpa	720 / 72	
tonnage	t	60	
stroke	mm	150	
closed height	mm	363	
capacity	kN/t	606 / 61.8	
effective pressure area	Cm <sup>2</sup>	84.2	
required oil content (effective)	СС	1263	
connection		A 118	
cylinder type		hollow plunger	
acting type		single	
return type		spring	
material		aluminium	
weight, ready for use	kg	21.8	
ASME		B30.1	



holmat

mastering **po**v

ro



Technical drawing dimensions		
dimension A	mm	363
dimension B	mm	186
dimension C	mm	110
dimension D	mm	80
dimension E	mm	33
dimension F	mm	276
dimension G	mm	43.5
dimension H	mm	150
dimension R	mm	56
angle A1	o	40

#### Standard supplied with

High flow female coupler A118
Hollow saddle; prevents damage to the plunger

• Larger cylinders are equipped with foldable handles for easy carrying and positioning

### Accessories

Saddle TRS60

100.003.655



#### holmatro.com

© Holmatro 2023-11-29

While the greatest care has been devoted to the content, it is possible that the information in this printed matter is incorrect or incomplete. Holmatro B.V. and its affiliated companies (hereafter: Holmatro) cannot be held liable in any way for the consequences of activities undertaken on the basis of this printed matter. Values can vary within the manufacturer measurements. If you have any doubts about the correctness or completeness of the information, you shall contact Holmatro (T+31 (0)162-751480). Nothing from this printed matter can be copied and/or made public in any way without the explicit authorisation of Holmatro.