
Technical specification sheet



HATC 127/53 H 20 | Telescopic Cylinder

Specifications		
article number		101.001.173
short description		Telescopic Cylinder
model		HATC 127/53 H 20
max. working pressure	psi	7977
stroke 1st plunger	in	3.7
stroke 2nd plunger	in	4.2
closed height	in	10.4
max. side-load resistance	%	10
capacity 1st plunger	lbf	280562
capacity 2nd plunger	lbf	117575
required oil content (effective)	OZ	78.3
required oil content (press)	OZ	105.8
required oil content (retract)	OZ	27.5
cylinder type		telescopic
acting type		double
return type		hydraulic
material		aluminium
weight, ready for use	lb	62.8





Technical drawing dimensions			
dimension A	in	9.6	
dimension B	in	8.9	
dimension B2	in	9.1	
dimension C1	in	5.9	
dimension C2	in	3.5	
dimension D	in	1.7	
dimension E	in	3	
dimension F	in	10.4	
dimension G	in	0.8	
dimension R	in	8.9	
dimension T	in	5.6	
dimension U	in	1.2	
dimension V	in	3.3	

Accessories	
Stacking Ring SR127/53-50	101.001.626
Stacking Ring SR127/53-100	101.001.627

holmatro.com

© Holmatro 2023-12-29

While the greatest care has been devoted to the content, it is possible that the information in this printed matter is incorrect or incomplete. Holmatro B.V. and its affiliated companies (hereafter: Holmatro) cannot be held liable in any way for the consequences of activities undertaken on the basis of this printed matter. Values can vary within the manufacturer measurements. If you have any doubts about the correctness or completeness of the information, you shall contact Holmatro (T +31 (0)162-751480). Nothing from this printed matter can be copied and/or made public in any way without the explicit authorisation of Holmatro.