

## **HGC 10 S 20** | Multi Purpose Cylinder


Specifications		
article number		100.112.222
short description		Multi Purpose Cylinder
model		HGC 10 S 20
max. working pressure	psi	10443
tonnage	lb	22046.0
stroke	in	7.9
closed height	in	11.4
capacity	lbf	22481
effective pressure area	sq. in.	2.2
required oil content (effective)	OZ	9.4
connection		A 118
cylinder type		multi purpose
acting type		single
return type		spring
material		steel
weight, ready for use	lb	12.1
ASME		B30.1

Technical drawing dimensions			
dimension A	in	11.4	
dimension B	in	2.4	
dimension C1	in	1.5	
dimension C2	in	0.8	
dimension D	in	3.1	
dimension E	in	0.8	
dimension F	in	11.3	
dimension G	in	0.2	
dimension J	threadsize	21/4"-14-UNS	
dimension K	in	1.2	
dimension L	threadsize	1"-8-UNC	
dimension M	in	0.8	
dimension N	in	1.6	
dimension O	threadsize	M8x12 (2x)	
angle A1	0	90	

## Standard supplied with

- Collar thread and base mounting holes
- Internal plunger thread on all models to 50 tons
- High flow female coupler A118
- Flat saddle







## holmatro.com