
Technical specification sheet

HHJ 30 G 5 Hollow Plunger Cylinder

Specifications			
article number		100.111.053	
short description		Hollow Plunger Cylinder	
model		HHJ 30 G 5	
max. working pressure	bar/Mpa	720 / 72	
tonnage	t	30	
stroke	mm	50	
closed height	mm	120	
capacity	kN/t	293.7 / 29.9	
effective pressure area	Cm ²	40.8	
required oil content (effective)	CC	204	
connection		A 118	
cylinder type		hollow plunger	
acting type		single	
return type		gravity	
material		steel	
weight, ready for use	kg	10.0	



holmatro mastering power



Technical drawing dimensions		
dimension A	mm	120
dimension B	mm	118
dimension C	mm	70
dimension D	mm	90
dimension E	mm	33
dimension F	mm	120
dimension R	mm	33
dimension S	threadsize	-

Standard supplied with

• High flow female coupler A118

Accessories		
Nut Tension Rod NUT 30	100.581.013	
Tension Rod, HTB 30	100.581.003	



holmatro.com

© Holmatro 2024-03-18

While the greatest care has been devoted to the content, it is possible that the information in this printed matter is incorrect or incomplete. Holmatro B.V. and its affiliated companies (hereafter: Holmatro) cannot be held liable in any way for the consequences of activities undertaken on the basis of this printed matter. Values can vary within the manufacturer measurements. If you have any doubts about the correctness or completeness of the information, you shall contact Holmatro (T +31 (0)162-751480). Nothing from this printed matter can be copied and/or made public in any way without the explicit authorisation of Holmatro.