Technical specification sheet


HHJ 30 G 5 Hollow Plunger Cylinder

Specifications		
article number		100.111.053
short description		Hollow Plunger Cylinder
model		HHJ 30 G 5
max. working pressure	psi	10443
tonnage	lb	66139.0
stroke	in	2
closed height	in	4.7
capacity	lbf	66026
effective pressure area	sq. in.	6.3
required oil content (effective)	OZ	6.9
connection		A 118
cylinder type		hollow plunger
acting type		single
return type		gravity
material		steel
weight, ready for use	dl	22.0



holmatro

mastering powe



Technical drawing dimensions		
dimension A	in	4.7
dimension B	in	4.6
dimension C	in	2.8
dimension D	in	3.5
dimension E	in	1.3

Standard supplied with

dimension F

dimension R

dimension S

• High flow female coupler A118

Accessories		
Nut Tension Rod NUT 30	100.581.013	
Tension Rod, HTB 30	100.581.003	

in

in

threadsize

4.7

1.3

-



holmatro.com

© Holmatro 2024-03-18

While the greatest care has been devoted to the content, it is possible that the information in this printed matter is incorrect or incomplete. Holmatro B.V. and its affiliated companies (hereafter: Holmatro) cannot be held liable in any way for the consequences of activities undertaken on the basis of this printed matter. Values can vary within the manufacturer measurements. If you have any doubts about the correctness or completeness of the information, you shall contact Holmatro (T +31 (0)162-751480). Nothing from this printed matter can be copied and/or made public in any way without the explicit authorisation of Holmatro.