
Technical specification sheet



HJ 150 G 15 SN | Locknut Cylinder

Specifications			
article number		100.112.136	
short description		Locknut Cylinder	
model		HJ 150 G 15 SN	
max. working pressure	bar/Mpa	720 / 72	
tonnage	t	150	
stroke	mm	150 363 1538.9 / 156.9	
closed height	mm		
capacity	kN/t		
effective pressure area	Cm ²	213.8	
required oil content (effective)	CC	3207	
connection		A 118	
cylinder type		lock nut	
acting type		single	
return type		gravity	
material		steel	
weight, ready for use	kg	101.0	





Technical drawing dimensions				
dimension A	mm	363		
dimension B	mm	212		
dimension C	mm	165		
dimension D	mm	70		
dimension E	mm	35		
dimension F	mm	305		
I type		[11]		

Standard supplied with

High flow female coupler A118Flat saddle

Accessories	
Tilting Saddle HJ 200 - 250 (SN)	100.999.040



holmatro.com

© Holmatro 2024-01-09

While the greatest care has been devoted to the content, it is possible that the information in this printed matter is incorrect or incomplete. Holmatro B.V. and its affiliated companies (hereafter: Holmatro) cannot be held liable in any way for the consequences of activities undertaken on the basis of this printed matter. Values can vary within the manufacturer measurements. If you have any doubts about the correctness or completeness of the information, you shall contact Holmatro (T +31 (0)162-751480). Nothing from this printed matter can be copied and/or made public in any way without the explicit authorisation of Holmatro.