

Technical specification sheet

HJ 150 G 30 | Cylinder

Specifications		
article number		100.112.047
short description		Cylinder
model		HJ 150 G 30
max. working pressure	bar/Mpa	720 / 72
tonnage	t	150
stroke	mm	300
closed height	mm	502
capacity	kN/t	1538.9 / 156.9
effective pressure area	cm ²	213.8
required oil content (effective)	cc	6414
connection		A 118
cylinder type		high tonnage
acting type		single
return type		gravity
material		steel
weight, ready for use	kg	125.3

Technical drawing dimensions		
dimension A	mm	502
dimension B	mm	227
dimension C	mm	115
dimension D	mm	70
dimension E	mm	57
dimension F	mm	495
I type		[I1]

Standard supplied with	
<ul style="list-style-type: none"> • High flow female coupler A118 • Flat saddle 	

Accessories	
Tilting Saddle HJ 100 - 150 (SN)	100.181.044



holmatro.com

© Holmatro 2024-01-09

While the greatest care has been devoted to the content, it is possible that the information in this printed matter is incorrect or incomplete. Holmatro B.V. and its affiliated companies (hereafter: Holmatro) cannot be held liable in any way for the consequences of activities undertaken on the basis of this printed matter. Values can vary within the manufacturer measurements. If you have any doubts about the correctness or completeness of the information, you shall contact Holmatro (T +31 (0)162-751480). Nothing from this printed matter can be copied and/or made public in any way without the explicit authorisation of Holmatro.