
Technical specification sheet



HJ 50 G 6 Cylinder

Specifications		
article number		100.112.073
short description		Cylinder
model		HJ 50 G 6
max. working pressure	bar/Mpa	720 / 72
tonnage	t	50
stroke	mm	60
closed height	mm	142
capacity	kN/t	510.3 / 52
effective pressure area	CM ²	70.9
required oil content (effective)	CC	425
connection		A 118
cylinder type		high tonnage
acting type		single
return type		gravity
material		steel
weight, ready for use	kg	12.5





Technical drawing dimensions		
dimension A	mm	142
dimension B	mm	130
dimension C	mm	80
dimension D	mm	70
dimension E	mm	20
dimension F	mm	135

Standard supplied with

High flow female coupler A118Flat saddle

Tilting Saddle S 50 TN 100.181.043	



holmatro.com

© Holmatro 2024-03-18

While the greatest care has been devoted to the content, it is possible that the information in this printed matter is incorrect or incomplete. Holmatro B.V. and its affiliated companies (hereafter: Holmatro) cannot be held liable in any way for the consequences of activities undertaken on the basis of this printed matter. Values can vary within the manufacturer measurements. If you have any doubts about the correctness or completeness of the information, you shall contact Holmatro (T+31 (0)162-751480). Nothing from this printed matter can be copied and/or made public in any way without the explicit authorisation of Holmatro.