

Technical specification sheet

IPU-M 12 W 06 D | Mobile Pump

Specifications			
article number			170.152.039
model			IPU-M 12 W 06 D
max. working pressure	psi		7252
for cutter type			mobile
short description			Mobile Pump
capacity oil tank (effective)	oz		202.9
number of stages			2
first stage output / min.	oz		108.2
second stage output / min.	oz		40.6
first stage pressure range	psi		0 - 2901
second stage pressure range	psi		2901 - 7252
operator type			electric motor
engine			230 VAC - 1.5 kW - 50 Hz - 1 Ph
weight, ready for use	lb		103.6
dimensions (LxWxH)	in		18.2 x 13.3 x 18.5

Standard supplied with			
<ul style="list-style-type: none"> • Protection frame (IPU-M 2035 DRU / PRU) 			



holmatro.com

© Holmatro 2024-04-29

While the greatest care has been devoted to the content, it is possible that the information in this printed matter is incorrect or incomplete. Holmatro B.V. and its affiliated companies (hereafter: Holmatro) cannot be held liable in any way for the consequences of activities undertaken on the basis of this printed matter. Values can vary within the manufacturer measurements. If you have any doubts about the correctness or completeness of the information, you shall contact Holmatro (T +31 (0)162-751480). Nothing from this printed matter can be copied and/or made public in any way without the explicit authorisation of Holmatro.