
Technical specification sheet

IPU-M 12 W 06 G | Mobile pump

Specifications		
article number		101.002.743
model		IPU-M 12 W 06 G
max. working pressure	bar/Mpa	500 / 50
for cutter type		mobile
short description		Mobile pump
capacity oil tank (effective)	CC	6000
number of stages		2
first stage output / min.	CC	3200
second stage output / min.	CC	1200
first stage pressure range	bar/Mpa	0 - 200 / 0 - 20
second stage pressure range	bar/Mpa	200 - 500 / 20 - 50
operator type		electric motor
engine		110/120 VAC - 60 Hz - 1 Ph
weight, ready for use	kg	47.0
dimensions (LxWxH)	mm	462 x 339 x 470

Accessories		
Cover Plate for Protection Frame	100.151.040	
Protection Frame - Vari Pumps	100.151.056	





holmatro.com

© Holmatro 2024-05-08

While the greatest care has been devoted to the content, it is possible that the information in this printed matter is incorrect or incomplete. Holmatro B.V. and its affiliated companies (hereafter: Holmatro) cannot be held liable in any way for the consequences of activities undertaken on the basis of this printed matter. Values can vary within the manufacturer measurements. If you have any doubts about the correctness or completeness of the information, you shall contact Holmatro (T +31 (0)162-751480). Nothing from this printed matter can be copied and/or made public in any way without the explicit authorisation of Holmatro.

