Technical specification sheet



IPU-M 32 S 25 E Extremely Durable Pump

Specifications		
article number		170.152.503
model		IPU-M 32 S 25 E
max. working pressure	bar/Mpa	350 / 35
for cutter type		mobile
short description		Extremely Durable Pump
capacity oil tank (effective)	СС	25000
number of stages		1
first stage output / min.	СС	3200
first stage pressure range	bar/Mpa	0 - 350 / 0 - 35
operator type		electric motor
engine		400 VAC - 2.2 kW - 50 Hz - 3 Ph
weight, ready for use	kg	72.0
dimensions (LxWxH)	mm	528 x 400 x 651

Accessories	
Cover Plate for Protection Frame	100.151.040
Protection Frame - Vari Pumps	100.151.056



holmatro.com

© Holmatro 2024-05-02

While the greatest care has been devoted to the content, it is possible that the information in this printed matter is incorrect or incomplete. Holmatro B.V. and its affiliated companies (hereafter: Holmatro) cannot be held liable in any way for the consequences of activities undertaken on the basis of this printed matter. Values can vary within the manufacturer measurements. If you have any doubts about the correctness or completeness of the information, you shall contact Holmatro (T +31 (0)162-751480). Nothing from this printed matter can be copied and/or made public in any way without the explicit authorisation of Holmatro.